AD

Research and Development Technical Report
ECOM- 0296-3

AD668942

BALLISTIC WINDS STUDY

QUARTERLY REPORT

REPORT NO. 3

BY

FREDERICK P. OSTBY, JR.

MAY 1968



ECOM

UNITED STATES ARMY ELECTRONICS COMMAND · FORT MONMOUTH, N.J.

CONTRACT NO. DAAB07-67-C0296

THE TRAVELERS RESEARCH CENTER, INC.
250 CONSTITUTION PLAZA, HARTFORD, CONNECTICUT 06103

DISTRIBUTION STATEMENT

This document has been approved for public release and sale; its distribution is unlimited.

Reproduced by the
CLEARINGHOUSE
for Federal Scientific & Technical
Information Springfield Va 22151

30



NOTICES

Disclaimers

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The citation of trade names and names of manufacturers in this report is not to be construed as official Government indorsement or approval of commercial products or services referenced herein.

Disposition

Destroy this report when it is no longer needed. Do not return it to the originator.

TECHNICAL REPORT ECOM-0296-3

Reports Control Symbol
OSD-1366

May 1968

BALLISTIC WINDS STUDY

Quarterly Report

Report No. 3

1 September 1967 to 30 November 1967

Contract No. DAAB07-67-C0296

Project No. 1T0-25001-A-126-01-19

Prepared by

Frederick P. Ostby, Jr.

THE TRAVELERS RESEARCH CENTER, INC.
250 Constitution Plaza
Hartford, Connecticut
06103

for

U.S. ARMY ELECTRONICS COMMAND, FORT MONMOUTH, N.J.

DISTRIBUTION STATEMENT

This document has been approved for public release and sale; its distribution is unlimited.

ABSTRACT

Some preliminary analyses were derived from the CRAM objective analysis program. The program has been generalized so that various grid intervals may be conveniently tested. There also has been a modification which will permit use of a cathode-ray tube to generate maps of the program output.

Two sets of analyses were made. One used a 10-km grid interval while the other used a finer 5-km grid interval. The finer grid mesh analysis fits the data more closely than the 10-km grid.

TABLE OF CONTENTS

Section	Title	Page
1.0	INTRODUCTION	1
2.0	ADDITIONAL PROGRAM FEATURES	3
3.0	PRELIMINARY ANALYSIS TESTS	7
	DISTRIBUTION LIST	25
	DD Form 1473	31

LIST OF ILLUSTRATIONS

Figure	Title	Page
2-1	Schematic representation showing how stations are assigned to gridpoints in the initial-guess procedure for a case in which the basic grid interval is 10km	4
3-1	Zone 1, u-component analysis (knots). 10-km grid. 0800 MST 6 Feb 1965	9
3-2	Zone 1, u-component analysis (knots). 5-km grid. 0800 MST 6 Feb 1965	10
3-3	Zone 4, u-component analysis (knots). 10-km grid. 0800 MST 6 Feb 1965	11
3-4	Zone 4, u-component analysis (knots). 5-km grid. 0800 MST 6 Feb 1965	12
3-5	Zone 7, u-component analysis (knots). 10-km grid. 0800 MST 6 Feb 1965	13
3-6	Zone 7, u-component analysis (knots). 5-km grid. 0800 MST 6 Feb 1965	14
3-7	Zone 10, u-component analysis (knots). 10-km grid. 0800 MST 6 Feb 1965	15
3-8	Zone 10, u-component analysis (knots). 5-km grid. 0800 MST 6 Feb 1965	16
3-9	Zone 1, v-component analysis (knots). 10-km grid. 0800 MST 6 Feb 1965	17
3-10	Zone 1, v-component analysis (knots). 5-km grid. 0800 MST 6 Feb 1965	18

Figure	Title	Page
3-11	Zone 4, v-component analysis (knots). 10-km grid. 0800 MST 6 Feb 1965	19
3-12	Zone 4, v-component analysis (knots). 5-km grid. 0800 MST 6 Feb 1965	20
3-13	Zone 7, v-component analysis (knots). 10-km grid. 0800 MST 6 Feb 1965	21
3-14	Zone 7, v-component analysis (knots). 5-km grid. 0800 MST 6 Feb 1965	22
3-15	Zone 10, v-component analysis (knots). 10-km grid. 0800 MST 6 Feb 1965	23
3-16	Zone 10, v-component analysis (knots), 5-km grid. 0800 MST 6 Feb 1965	24

1.0 INTRODUCTION

This report describes technical progress during the third quarter, September 1, 1967 through November 30, 1967 of the contract year, under Contract DAAB07-67-C0296, "Ballistic Winds Techniques Study."

The primary emphasis during this quarter was directed toward experimentation with the CRAM (Conditional Relaxation Analysis Method) objective analysis program. The program has been generalized so that the grid interval may be specified as an input parameter, thus permitting testing of more than one grid mesh. During this past quarter, tests were initiated using several grid intervals and some examples are included herein. These tests are continuing into the fourth quarter.

Additional versatility and refinements have been incorporated into the analysis program package. Nearly all of this development effort has been accomplished within other contracts and therefore has not required expenditure of resources from this project. Some of these features which are applicable to our project are discussed in this report.

2.0 ADDITIONAL PROGRAM FEATURES

Several new features available in the CRAM computer program package have been incorporated for use in the Ballistic Winds Study. There are other features which could be used at some future time.

One new feature being used is a revised initial guess procedure. Our previous initial-guess field generation was accomplished by the use of a surface-fitting technique in which the independent variables were derived using a screening multiple regression procedure. This scheme had the weakness that although the surface fit would yield fairly representative values over the interior regions of the analysis area, the values near the edges of the grid or away from data areas were unrealistic at times. An alternative method was formulated which is computationally quicker, yields more representative values, and also incorporates information from other levels (zones) through a build-up procedure.

In this scheme, we make use of a very coarse grid (40 km between grid points). Each station location is assigned to the grid point nearest it (see Fig. 2-1). The difference (C) is computed between each station's observation value (ϕ_k) and the corresponding analyzed value from the level below ($\hat{\phi}_{k-1}$) at that station's horizontal coordinates, i.e., $C = (\phi_k - \hat{\phi}_{k-1})$. The differences represent corrections which are applied to grid points on the coarse grid. Overall corrections ($\tilde{C}$) are then computed for each grid point of the coarse grid from the following:

$$\tilde{C}_{i,j} = \frac{\left(\sum_{n=1}^{N} C_n\right)_{i,j}}{N_{i,j}} \qquad \begin{array}{l} \text{for } i = 1,5,9, \ldots, \text{etc.} \\ \quad\; j = 1,5,9, \ldots, \text{etc.} \end{array} \qquad (2\text{-}1)$$

Thus it can be seen that (1) the overall corrections are computed for only grid points of the coarse grid and (2) if more than one station is associated with a grid point, the overall correction is the average of the "n" individual corrections.

Those coarse grid points which have no stations assigned are corrected by a simple scanning procedure. The grid-point values are then smoothed. Conversion is then made back to the standard size grid with the values at the initial grid points being generated by interpolation. This field of corrections is then added to the analysis of the level below to generate the initial guess field.



Fig. 2-1. Schematic representation showing how stations are assigned to gridpoints in the initial-guess procedure for a case in which the basic grid interval is 10km.

A second new feature of the program is that the distance between grid points is now an input parameter which means that analyses using various grid intervals can be tested and compared. Initial testing of the basic 10-km grid interval being used and a proposed finer grid of 5 km was conducted. Some examples of this are shown in the next section.

One additional feature being employed involves an alternative form of computer output. Contoured maps can now be generated using a cathode-ray tube. The program outputs a tape which contains x,y-coordinates for points on lines representing each isopleth. This tape is fed into a cathode-ray tube (Stromberg Carlson 4020) and activates an electron beam which traces out the x,y-coordinate of the isopleths, the observational

data, and any analyzed maxima or minima. A camera photographs the image on the cathode-ray tube and thereby provides output in the form of prints and/or microfilm. To illustrate this feature, analyses of 5-km and 10-km zone winds are included in this form in the next section. Standard contoured analyses in computer printout form are optionally available through use of an input parameter in the program.

Another feature, but not being used at this time, is an option in the program which permits alternative analysis techniques to be used. One of these is the so-called successive approximative technique (SAT). Additional features permit calculation of special fields such as stream function, divergence, and vorticity.

3.0 PRELIMINARY ANALYSIS TESTS

A limited test was conducted of the analysis program using the 5-km grid spacing (i.e., half the grid interval which had been used for previous tests). For zones 1, 4, 7, and 10, 0800 MST 6 February 1965, u, v-zone wind components were analyzed using both the 5- and 10-km grid intervals. The cathode-ray tube was used to generate the output which is shown in Figs. 3-1 through 3-16.

The contours are formed in this procedure by the connection of line segments which is the reason for the lack of curvature of the contours. This problem can be easily overcome by using a finer output grid. There are two intensities of lines. The darker lines represent each 5 knots. There is no automatic labelling of isopleths, but the appropriate labels can be inferred from the plotted data. The lighter of the two sets of numbers represents the observational data where the decimal point represents the observation location. The darker numbers are maxima and minima of the analysis. These are defined as values higher (or lower) than the eight surrounding grid points. The grid region is similar to that used previously. That is, the grid locations range from 50 to 66 in the "x" direction and from 345 to 361 in the "y" direction. The same region is used for the 5-km grid except that the grid units are 50.0, 50.5, 51.0, etc., giving a 33 by 33 grid network as opposed to the 17 by 17 grid using the 10-km spacing.

This type of output allows for more convenient visual inspection than does the machine contoured printout page, especially when it is noted that the fine-grid output would require four pages of printout pasted together to portray the analysis. One can also see both the analysis and the observational data on the same map.

Some of the shortcomings of this type of output are the lack of curvature of isopleths, the absence of labels for contours, and the occasional observation of numbers when data and extrema are located near one another.

Examinations of Figs. 3-1 through 3-16 shows that the finer mesh allows for the inclusion of much more detail than does the 10-km grid. As one would expect, the analyses on the finer grid (33 by 33) fit the observational data more closely than do the analyses on the 17 by 17 grid. There is a tendency for more closed centers to be analyzed on the finer grid. For example, the zone 4 u-component analyses (Figs. 3-3 and 3-4 show a single maximum in the lower left with a value of 25.3 for the 10-km

grid (Fig. 3-3), whereas there are two centers of maximum "u" of 24.4 and 24.3 knots in the 5-km grid analysis shown in Fig. 3-4. One method of making a comparative evaluation of the two analyses is to compare them on the basis of ballistic corrections derived from them and applied to the concurrent artillery firings which took place during the data collection. This will be done during the next contract interval.



Fig. 3-1. Zone 1, u-component analysis (knots). 10-km grid. 0800 MST 6 Feb 1965.



Fig. 3-2. Zone 1, u-component analysis (knots). 5-km grid. 0800 MST 6 Feb 1965.



Fig. 3-3. Zone 4, u-component analysis (knots). 10-km grid. 0800 MST 6 Feb 1965.



Fig. 3-4. Zone 4, u-component analysis (knots). 5-km grid. 0800 MST 6 Feb 1965.



Fig. 3-5. Zone 7, u-component analysis (knots). 10-km grid. 0800 MST 6 Feb 1965.



Fig. 3-6. Zone 7, u-component analysis (knots). 5-km grid. 0800 MST 6 Feb 1965.



Fig. 3-7. Zone 10, u-component analysis (knots). 10-km grid. 0800 MST 6 Feb 1965.



Fig. 3-8. Zone 10, u-component analysis (knots). 5-km grid. 0800 MST 6 Feb 1965.



Fig. 3-9. Zone 1, v-component analysis (knots). 10-km grid. 0800 MST 6 Feb 1965.



Fig. 3-10. Zone 1, v-component analysis (knots). 5-km grid. 0800 MST 6 Feb 1965.



Fig. 3-11. Zone 4, v-component analysis (knots). 10-km grid. 0800 MST 6 Feb 1965.



Fig. 3-12. Zone 4, v-component analysis (knots). 5-km grid. 0800 MST 6 Feb 1965.



Fig. 3-13. Zone 7, v-component analysis (knots). 10-km grid. 0800 MST 6 Feb 1965.



Fig. 3-14. Zone 7, v-component analysis (knots). 5-km grid. 0800 MST 6 Feb 1965.



Fig. 3-15. Zone 10, v-component analysis (knots). 10-km grid. 0800 MST 6 Feb 1965.



Fig. 3-16. Zone 10, v-component analysis (knots). 5-km grid. 0800 MST 6 Feb 1965.

Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1 ORIGINATING ACTIVITY (Corporate author) The Travelers Research Center, Inc. 250 Constitution Plaza Hartford, Connecticut 06103	2a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED 2b GROUP N/A

3. REPORT TITLE

Ballistic Winds Study

4. DESCRIPTIVE NOTES (Type of report and inclusive dates)

Quarterly Report No. 3, 1 September 1967 to 30 November 1967

5. AUTHOR(S) (Last name, first name, initial)

Ostby, Frederick, P.

6. REPORT DATE	7a. TOTAL NO. OF PAGES	7b. NO. OF REFS
March 1968	32 + iv	None

8a. CONTRACT OR GRANT NO.	9a. ORIGINATOR'S REPORT NUMBER(S)
DAAB07-67-C0296 b. PROJECT NO. c. 1T0-25001-A-126-01-19 d.	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report) ECOM-0296-3

10. AVAILABILITY/LIMITATION NOTICES

This document has been approved for public release and sale; its distribution is unlimited.

11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY
None	U.S. Army Electronics Command ATTN: AMSEL-BL-TE Ft. Monmouth, N. J. 07703

13. ABSTRACT

Some preliminary analyses were derived from the CRAM objective analysis program. The program has been generalized so that various grid intervals may be conveniently tested. There also has been a modification which will permit use of a cathode-ray tube to generate maps of the program output.

Two sets of analyses were made. One used a 10-km grid interval while the other used a finer 5-km grid interval. The finer grid mesh analysis fits the data more closely than the 10-km grid.

DD FORM 1 JAN 64 1473

Security Classification

Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Ballistic Map Winds Ballistic Metro Corrections Zone-Winds						

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization *(corporate author)* issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers *(either by the originator or by the sponsor)*, also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

(1) "Qualified requesters may obtain copies of this report from DDC."

(2) "Foreign announcement and dissemination of this report by DDC is not authorized."

(3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."

(4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."

(5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring *(paying for)* the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as *(TS), (S), (C), or (U)*.

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, roles, and weights is optional.